

Product Information

HES5A/8A Series

5 and 8-port Din-rail Unmanaged Ethernet Switches



Features

- ❖ UL/cUL Class I Division 2 Groups A,B,C, and D
- ❖ Shock, vibration, tested
- ❖ 10/100M, full/half duplex, MDI/MDI-X (Auto-negotiate)
- ❖ Industrial IP30 rated DIN rail case with 6 way panel mount options
- ❖ Dual power inputs, 12 to 36 VDC and 10 to 24 VAC
- ❖ Operating temperature:-10°C to 60°C (Standard); -40°C to 75°C (W models)
- ❖ 100% burn in testing

HENRICHTM
Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

Designed to fit Industrial and Commercial applications, the HES5A (5 ports) and HES8A (8 ports) series are plug and play Ethernet switches with compact IP30 DIN rail enclosure, 6 way panel mounting. Convenient LEDs for Power, (Link / Speed / Activity for each port). Powering options include 12 to 36 VDC or 10 to 24 VAC.

Choose a switch with copper ports, or a combination of copper and fiber ports. Multi-mode fiber models extend range up to 2 km. Single-mode fiber models extend range up to 20 km. All models require an external power supply (sold separately).

The switch ships with 4 panel mount clips giving the user 6 different ways to panel mount the unit.

Specifications

Technology		Environment Limits		
Standard :	IEEE802.3, 802.3u, 802.3x	Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C	
Processing Type :	Store and Forward	Storage Temp. :	-40 to 85°C	
Broadcast Storm :	Automatic Broadcast Storm Control	Ambient Relative Humidity :	5 to 95%(Non-condensing)	
Flow Control :	Full Duplex Flow Control, Half Duplex Back Pressure Control	Optical Fiber		
Protocols :	CSMA/CD (Carrier Sense Multiple Access/Collision Direct)	Mode	Multi-mode	Single Mode
Switch Properties		Transmission Distance	2km	20km
MAC Table Size :	2K	Centre Wavelength	1310nm	1310nm
Interface		Cable Size	62.5/125um	9/125um
RJ45 Port :	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	TX Power(dBm)	-20~-10dBm	-15~-8dBm
Fiber Port :	100BaseFX ports (SC/ST connector)	RX Power(dBm)	< -32dBm	< -32dBm
LED Indicators :	Power, (Link / Speed / Activity for each port)	Transmission Rate	100Mbps	100Mbps
Power Requirements		Standards and Certifications		
Input Voltage :	HES5A: 12~36VDC @ 6.5W MAX; 10~24VAC @ 6.5VA MAX;	Safety :	cUL508	
	HES8A: 12~36VDC @ 12.5W MAX; 10~24VAC @ 12.5VA MAX;	EMI :	FCC Part15, CISPR(EN55022) Class A EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2 UL Class 1, Division 2, Groups A, B, C, and D	
Input Connection :	Standard four terminal power input	EMS :		
Physical Characteristics		Shock :	IEC 60068-2-27	
Case :	Slim Metal Case, IP30 Design	Freefall :	IEC 60068-2-32	
Dimensions :	30×112.4×75.2mm (HES5A) 46×130×105mm (HES8A)	Vibration :	IEC 60068-2-6	
Installation :	DIN Rail or Panel Mounting	Warranty		
		Warranty Period :	3 years	

Ordering Information

HES5A

HES5A-VL	Din-rail Unmanaged, 5 x 100Mbps Copper Port, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-VLW	Din-rail Unmanaged, 5 x 100Mbps Copper Port, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES5A-SC-VL	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 1 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-SC-VLW	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 1 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-SSC-VL	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 1 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-SSC-VLW	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 1 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES5A-2SC-VL	Din-rail Unmanaged, 3 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-2SC-VLW	Din-rail Unmanaged, 3 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES5A-2SSC-VL	Din-rail Unmanaged, 3 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES5A-2SSC-VLW	Din-rail Unmanaged, 3 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector

HES8A

HES8A-VL	Din-rail Unmanaged, 8 x 100Mbps Copper Port, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES8A-VLW	Din-rail Unmanaged, 8 x 100Mbps Copper Port, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES8A-2SC-VL	Din-rail Unmanaged, 6 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES8A-2SC-VLW	Din-rail Unmanaged, 6 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES8A-2SSC-VL	Din-rail Unmanaged, 6 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES8A-2SSC-VLW	Din-rail Unmanaged, 6 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES8A-4SC-VL	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES8A-4SC-VLW	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC
HES8A-4SSC-VL	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Temperature -10~+60°C, Power Input 12~36VDC or 10~24VAC
HES8A-4SSC-VLW	Din-rail Unmanaged, 4 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC Connectors, 20KM, Industrial Wide Temperature -40~+75°C, Power Input 12~36VDC or 10~24VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector